Vitillo

CRIMPING PARAMETERS CHART

BRAIDED HOSES
Tubi trecciati

NOMINAL BORE	DN	5	6	8	10	12	16	19	25	31	38	51
INTERNAL DIAMETER	inches	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"	2"
	mm	4.8	6.4	7.9	9.5	12.8	16	19	25.4	31.8	38.1	50.8
TEKNO/1SN /1SNRW EN 853 1SN - SAE100 R1AT	B12T..N FOR STANDARD FITTINGS	.03: 16.0 (n.s.)	.04: 18.0 (n.s.)	.05: 18.6 (n.s.)	.06: 20.5 (n.s.)	.08: 23.4 (n.s.)	.10: 27.0 (n.s.)	.12: 30.8 (n.s.)	.16: 39.1 (n.s.)	.20: 48.5 (n.s.)	.24: 57.0 (n.s.)	.32: 69.4 (n.s.)
	B1SC FOR STANDARD FITTINGS	.04: 16.0 (n.s.)	.05: 17.8 (n.s.)	.06: 20.0 (n.s.)	.08: 23.6 (n.s.)	.10: 27.4 (n.s.)	.12: 30.2 (n.s.)	.16: 37.9 (n.s.)				
	B1T FOR STANDARD FITTINGS	.03: 15.4 (n.s.)	.04: 16.4 (n.s.)	.05: 18.2 (n.s.)	.06: 20.1 (n.s.)	.08: 24.2 (n.s.)	.10: 26.4 (n.s.)	.12: 30.8 (n.s.)	.16: 38.9 (n.s.)	.20: 46.6 (n.s.)	.24: 54.2 (n.s.)	
	B12T FOR STANDARD FITTINGS					.08: 23.5 (n.s.)	.10: 26.4 (n.s.)	.12: 30.8 (n.s.)				
TEKNO/2SN /2SNRW EN 853 2SN - SAE100 R2AT	B12T..N FOR STANDARD FITTINGS	.03: 16.7 (n.s.)	.04: 19.0 (n.s.)	.05: 19.6 (n.s.)	.06: 21.3 (n.s.)	.08: 24.4 (n.s.)	.10: 28.2 (n.s.)	.12: 32.0 (n.s.)	.16: 40.3 (n.s.)	.20: 51.0 (n.s.)	.24: 59.0 (n.s.)	.32: 72.7 (*4)
	B2T FOR STANDARD FITTINGS	.03: 15.7 (n.s.)	.04: 18.0 (n.s.)	.05: 20.2 (n.s.)	.06: 21.4 (n.s.)	.08: 25.6 (n.s.)	.10: 28.5 (n.s.)	.12: 32.0 (n.s.)	.16: 41.0 (n.s.)	.20: 50.0 (n.s.)	.24: 57.5 (n.s.)	
	B12T FOR STANDARD FITTINGS					.08: 24.4 (n.s.)	.10: 27.2 (n.s.)	.12: 32.0 (n.s.)				
TEKNO/1ST EN 853 1ST Nota / Note :	B1R.. FOR STANDARD FITTINGS	.03: 15.2 (1B)	.04: 17.2 (21)	.05: 18.8 (22)	.06: 21.0 (23)	.08: 25.4 (25)	.10: 28.2 (28)	.12: 32.2 (34)	.16: 39.8 (37)	.20: 46.6 (43)	.24: 53.0 (47)	.32: 66.2 (62)
TEKNO/2ST EN 853 2ST Nota / Note :	B2R.. FOR STANDARD FITTINGS	.03: 17.6 (1B.5)	.04: 17.8 (21)	.05: 20.3 (22)	.06: 23.0 (23)	.08: 25.7 (25)	.10: 29.0 (28)	.12: 33.5 (34)	.16: 41.2 (37)	.20: 50.8 (43)	.24: 56.7 (47)	.32: 69.5 (64)
TEKNO/1SC EXCEED AN857 1SC (scelta consigliata) (recommended option) Nota / Note :	B1SC.. FOR STANDARD FITTINGS	.04: 15.3 (n.s.)	.05: 16.8 (n.s.)	.06: 18.6 (n.s.)	.08: 22.5 (n.s.)	.10: 26.4 (n.s.)	.12: 29.2 (n.s.)	.16: 36.9 (*3)				
	B1K FOR STANDARD FITTINGS	.04: 15.0 (n.s.)	.05: 16.3 (n.s.)	.06: 18.6 (n.s.)	.08: 22.7 (n.s.)	.10: 26.4 (n.s.)	.12: 29.5 (n.s.)	.16: 37.9 (n.s.)	.20: 44.8 (n.s.)	.24: 50.8 (n.s.)	.32: 64.6 (n.s.)	
TEKNO/2SC EXCEED AN857 2SC (scelta consigliata) (recommended option) Nota / Note :	B12T..N FOR STANDARD FITTINGS	.04: 18.2 (n.s.)	.05: 19.0 (n.s.)	.06: 20.6 (n.s.)	.08: 23.5 (n.s.)	.10: 27.1 (n.s.)	.12: 31.1 (n.s.)	.16: 39.1 (n.s.)	.20: 48.7 (n.s.)	.24: 56.2 (n.s.)	.32: 71.0 (n.s.)	
	B1SC FOR STANDARD FITTINGS	.04: 16.2 (n.s.)	.05: 18.0 (n.s.)	.06: 20.0 (n.s.)	.08: 23.3 (n.s.)	.10: 27.6 (n.s.)	.12: 30.3 (n.s.)	.16: 37.9 (n.s.)				

BRAIDED HOSES
Tubi trecciati

NOMINAL BORE	DN	5	6	8	10	12	16	19	25	31	38	51
INTERNAL DIAMETER	inches	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"	2"
	mm	4.8	6.4	7.9	9.5	12.8	16	19	25.4	31.8	38.1	50.8
TEKNO/1SC PLUS EXCEED AN857 1SC Nota / Note :	B1SC FOR STANDARD FITTINGS	.04: 15.3 (n.s.)	.05: 16.8 (n.s.)	.06: 18.6 (n.s.)	.08: 22.5 (n.s.)	.10: 26.4 (n.s.)	.12: 29.2 (n.s.)	.16: 36.9 (*3)				
	B1K FOR STANDARD FITTINGS	.04: 15.0 (n.s.)	.05: 16.3 (n.s.)	.06: 18.6 (n.s.)	.08: 22.7 (n.s.)	.10: 26.4 (n.s.)	.12: 29.5 (n.s.)	.16: 37.9 (n.s.)	.20: 44.8 (n.s.)	.24: 50.8 (n.s.)	.32: 64.6 (n.s.)	
TEKNO/2SC PLUS EXCEED AN857 2SC (scelta consigliata) (recommended option) Nota / Note :	B12T..N FOR STANDARD FITTINGS	.04: 18.2 (n.s.)	.05: 19.0 (n.s.)	.06: 20.6 (n.s.)	.08: 23.5 (n.s.)	.10: 27.1 (n.s.)	.12: 31.1 (n.s.)	.16: 39.1 (n.s.)	.20: 48.7 (n.s.)	.24: 56.2 (n.s.)	.32: 71.0 (n.s.)	
	B1SC FOR STANDARD FITTINGS	.04: 16.2 (n.s.)	.05: 18.0 (n.s.)	.06: 20.0 (n.s.)	.08: 23.3 (n.s.)	.10: 27.6 (n.s.)	.12: 30.3 (n.s.)	.16: 37.9 (n.s.)				
FORTHREE	B2R FOR STANDARD FITTINGS	.04: 19.0 (21)		.04: 24.0 (23)	.06: 26.8 (25)	.08: 30.3 (28)	.10: 34.8 (34)	.12: 42.1 (37)				
	B5K FOR STANDARD				.06: 26.1 (n.s.)		.12: 36.6 (n.s.)	.16: 44.5 (n.s.)				
TEKNOMASTER 2SN	B2R FOR STANDARD FITTINGS	.04: 17.6 (21)	.05: 20.0 (22)	.06: 22.9 (23)	.08: 26.0 (25)	.10: 29.7 (28)	.12: 33.6 (34)	.16: 41.6 (37)				
STRONGER/1 SAE 100 R16 (scelta consigliata) (recommended option)	B1R FOR STANDARD FITTINGS	.03: 15.4 (1B)	.04: 17.3 (21)	.05: 18.6 (22)	.06: 20.5 (23)	.08: 25.2 (25)	.10: 27.4 (28)	.12: 31.0 (34)	.16: 39.0 (37)	.20: 45.7 (43)		
	B12T..N FOR STANDARD FITTINGS	.03: 16.2 (n.s.)	.04: 18.1 (n.s.)	.05: 18.4 (n.s.)	.06: 20.0 (n.s.)	.08: 23.2 (n.s.)	.10: 26.2 (n.s.)					
	B1SC FOR STANDARD FITTINGS		.04: 16.1 (n.s.)	.05: 17.6 (n.s.)	.06: 19.5 (n.s.)	.08: 23.4 (n.s.)	.10: 26.6 (n.s.)	.12: 29.0 (n.s.)	.16: 38.1 (n.s.)			
SLIM (scelta consigliata) (recommended option)	B1SC FOR STANDARD FITTINGS			.04: 15.0 (n.s.)	.05: 16.8 (n.s.)	.06: 18.2 (n.s.)	.08: 21.9 (n.s.)		.12: 28.7 (n.s.)			
	B1K FOR STANDARD FITTINGS			.04: 14.3 (n.s.)	.05: 15.7 (n.s.)	.06: 17.3 (n.s.)	.08: 21.7 (n.s.)		.16: 35.3 (n.s.)			
	B7R FOR STANDARD FITTINGS	.03: 12.3 (n.s.)										

*3 Note: Controllare con tampone No-Go diametro 19.65 mm
*3 Note: Check with No-Go gauge diameter 19.65 mm
*4 Note: Non effettuare il controllo del collasso con tampone Go, No-Go; Rispettare la quota indicata.
*4 Note: No check the diameter with Go, No-Go gauge; Respect the indicated diameter.

BRAIDED HOSES
Tubi trecciati

NOMINAL BORE	DN	5	6	8	10	12	16	19	25	31	38	51
INTERNAL DIAMETER	inches	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"	2"
	mm	4.8	6.4	7.9	9.5	12.8	16	19	25.4	31.8	38.1	50.8
TEKNOJACK	B12T..N FOR STANDARD FITTINGS		.04: 19.0 (n.s.)		.06: 20.3 (n.s.)							
LIFT-PLUS EN 81.2 (scelta consigliata) (recommended option)	B12T..N FOR STANDARD FITTINGS										.24: 56.8 (n.s.)	.32: 71.0 (n.s.)
	B1SC FOR STANDARD FITTINGS								.12: 29.2 (n.s.)	.16: 36.4 (n.s.)		
	B1R FOR STANDARD FITTINGS										.20: 45.6 (43)	
	B1K FOR STANDARD FITTINGS										.20: 44.6 (n.s.)	
	B1T20 FOR STANDARD FITTINGS										.20: 45.7 (n.s.)	
SERVOCOMANDO	B1SC FOR STANDARD FITTINGS		.04: 15.5 (n.s.)	.05: 17.0 (n.s.)	.06: 18.6 (n.s.)	.08: 22.5 (n.s.)						
ALPI 3300	B1SC FOR STANDARD FITTINGS		.04: 15.6 (ns)	.05: 16.9 (ns)	.06: 18.8 (ns)	.08: 22.5 (ns)	.10: 28.0 (ns)	.12: 30.5 (ns)	.16: 37.9 (ns)			
ALPI 4000 (scelta consigliata) (recommended option)	B12T..N FOR STANDARD FITTINGS		.04: 19.0 (n.s.)	.05: 20.6 (n.s.)	.06: 23.5 (n.s.)	.08: 27.3 (n.s.)	.10: 31.1 (n.s.)	.12: 39.0 (n.s.)	.16: 39.0 (n.s.)			
	B1SC FOR STANDARD FITTINGS		.04: 15.8 (ns)	.05: 18.0 (ns)	.06: 20.0 (ns)	.08: 23.8 (ns)	.10: 27.7 (ns)	.12: 30.3 (ns)	.16: 37.8 (ns)			
ICEBERG/1 EXCEED EN853 1SN SAE 100 R1AT	B1R FOR STANDARD FITTINGS	.03: 15.2 (1B)	.04: 17.2 (21)	.05: 18.8 (22)	.06: 21.0 (23)	.08: 25.4 (25)	.10: 28.2 (28)	.12: 32.2 (34)	.16: 39.8 (37)	.20: 46.6 (43)	.24: 53.0 (47)	.32: 66.2 (62)
ICEBERG/2 EXCEED EN853 2SN SAE 100 R2AT	B2R FOR STANDARD FITTINGS	.03: 17.6 (1B.5)	.04: 17.8 (21)	.05: 20.3 (22)	.06: 23.0 (23)	.08: 25.7 (25)	.10: 29.0 (28)	.12: 33.5 (34)	.16: 41.2 (37)	.20: 50.8 (43)	.24: 56.7 (47)	.32: 69.5 (64)

BRAIDED HOSES
Tubi trecciati

NOMINAL BORE	DN	5	6	8	10	12	16	19	25	31	38	51
INTERNAL DIAMETER	inches	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"	2"
	mm	4.8	6.4	7.9	9.5	12.8	16	19	25.4	31.8	38.1	50.8
ICEBERG/3	B2R FOR STANDARD FITTINGS		19.0 (21)		24.0 (23)	26.8 (25)	30.3 (28)	34.8 (34)	42.1 (37)			
VULCAN /1 EXCEED EN853 1SN SAE R1AT	B1R FOR STANDARD FITTINGS	.03: 15.2 (1B)	.04: 17.2 (21)	.05: 18.8 (22)	.06: 21.0 (23)	.08: 25.4 (25)	.10: 28.2 (28)	.12: 32.2 (34)	.16: 39.8 (37)	.20: 46.6 (43)	.24: 53.0 (47)	.32: 66.2 (62)
VULCAN /2 EXCEED EN853 2SN SAE R2AT	B2R.. FOR STANDARD FITTINGS	.03: 17.6 (1B.5)	.04: 17.8 (21)	.05: 20.3 (22)	.06: 23.0 (23)	.08: 25.7 (25)	.10: 29.0 (28)	.12: 33.5 (34)	.16: 41.2 (37)	.20: 50.8 (43)	.24: 56.7 (47)	.32: 69.5 (64)
VULCAN AIR EXCEED EN857 1SC (scelta consigliata) (recommended option)	BVA.. FOR STANDARD FITTINGS				.06: (a) 15.8 (b) 16.3	.08: (a) 21.0 (b) 21.5	.10: (a) 24.5 (b) 25.0	.12: (a) 27.8 (b) 28.3	.16: (a) 35.0 (b) 35.5	.20: (a) 41.2 (b) 41.7	.24: (a) 47.5 (b) 48.0	

blocchetto pressa

NOMINAL BORE	DN	5	6	8	10	12	16	19	25	31	38	51
INTERNAL DIAMETER	inches	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"	2"
	mm	4.8	6.4	7.9	9.5	12.8	16	19	25.4	31.8	38.1	50.8
PREMIER PREMIER RW	B12T..N FOR STANDARD FITTINGS		.04: 18.0 (n.s.)	.05: 18.8 (n.s.)	.06: 20.3 (n.s.)	.08: 23.2 (n.s.)	.10: 27.3 (n.s.)	.12: 31.3 (n.s.)	.16: 39.1 (n.s.)	.20: 48.1 (n.s.)	.24: 56.2 (n.s.)	.32: 68.7 (n.s.)
PREMIER ONE PREMIER ONE RW	B1K FOR STANDARD FITTINGS		.04: 14.6 (n.s.)	.05: 16.6 (n.s.)	.06: 17.8 (n.s.)	.08: 21.7 (n.s.)	.10: 25.8 (n.s.)	.12: 29.3 (n.s.)	.16: 36.4 (n.s.)			
SMART ONE (scelta consigliata) (recommended option)	B1K FOR STANDARD FITTINGS		.04: 14.6 (n.s.)	.05: 17.8 (n.s.)	.06: 21.7 (n.s.)	.08: 26.4 (n.s.)	.10: 29.5 (n.s.)	.12: 37.9 (n.s.)	.16: (n.s.)			
	B1SC FOR STANDARD FITTINGS		.04: 15.3 (n.s.)	.05: 16.8 (n.s.)	.06: (n.s.)	.08: 26.4 (n.s.)	.10: 29.2 (n.s.)	.12: 36.9 (n.s.)	.16: (n.s.)			
SMART TWO	B12T..N FOR STANDARD FITTINGS		.04: 18.0 (n.s.)	.05: 19.0 (n.s.)	.06: 20.6 (n.s.)	.08: 23.5 (n.s.)	.10: 27.4 (n.s.)	.12: 31.1 (n.s.)	.16: 39.1 (n.s.)			

BRAIDED HOSES
Tubi trecciati

NOMINAL BORE	DN	5	6	8	10	12	16	19	25	31	38	51
INTERNAL DIAMETER	inches	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"	2"
	mm	4.8	6.4	7.9	9.5	12.8	16	19	25.4	31.8	38.1	50.8
DOLOMITI/1SN EN 853 1SN - SAE100 R1AT (scelta consigliata) (recommended option)	B12T..N FOR STANDARD FITTINGS	.03: 16.0 (n.s.)	.04: 18.0 (n.s.)	.05: 18.6 (n.s.)	.06: 20.5 (n.s.)	.08: 23.4 (n.s.)	.10: 27.0 (n.s.)	.12: 30.8 (n.s.)	.16: 39.1 (n.s.)	.20: 48.5 (n.s.)	.24: 57.0 (n.s.)	.32: 69.4 (n.s.)
	B1SC FOR STANDARD FITTINGS		.04: 16.0 (n.s.)	.05: 17.8 (n.s.)	.06: 20.0 (n.s.)	.08: 23.6 (n.s.)	.10: 27.4 (n.s.)	.12: 30.2 (n.s.)	.16: 37.9 (n.s.)			
	B1T FOR STANDARD FITTINGS	.03: 15.4 (1B)	.04: 16.4 (21)	.05: 18.2 (22)	.06: 20.1 (23)	.08: 24.2 (25)	.10: 26.4 (28)	.12: 30.8 (34)	.16: 38.9 (37)	.20: 46.6 (43)	.24: 54.2 (47)	
	B12T FOR STANDARD FITTINGS					.08: 23.5 (n.s.)	.10: 26.4 (n.s.)	.12: 30.8 (n.s.)				
DOLOMITI/2SN EN 853 2SN - SAE100 R2AT (scelta consigliata) (recommended option)	B12T..N FOR STANDARD FITTINGS	.03: 16.7 (n.s.)	.04: 19.0 (n.s.)	.05: 19.6 (n.s.)	.06: 21.3 (n.s.)	.08: 24.4 (n.s.)	.10: 28.2 (n.s.)	.12: 32.0 (n.s.)	.16: 40.3 (n.s.)	.20: 51.0 (n.s.)	.24: 59.0 (n.s.)	.32: 72.3 (*4)
	B2T FOR STANDARD FITTINGS	.03: 15.7 (n.s.)	.04: 18.0 (n.s.)	.05: 20.2 (n.s.)	.06: 21.4 (n.s.)	.08: 25.6 (n.s.)	.10: 28.5 (n.s.)	.12: 32.0 (n.s.)	.16: 41.0 (n.s.)	.20: 50.0 (n.s.)	.24: 57.5 (n.s.)	
	B12T FOR STANDARD FITTINGS					.08: 24.4 (n.s.)	.10: 27.2 (n.s.)	.12: 32.0 (n.s.)				
DOLOMITI/1SC EXCEED AN857 1SC (scelta consigliata) (recommended option)	B1SC.. FOR STANDARD FITTINGS		.04: 15.3 (n.s.)	.05: 16.8 (n.s.)	.06: 18.6 (n.s.)	.08: 22.5 (n.s.)	.10: 26.4 (n.s.)	.12: 29.2 (n.s.)	.16: 36.9 (*3)			
	B1K FOR STANDARD FITTINGS	.04: 15.0 (n.s.)	.05: 16.3 (n.s.)	.06: 18.6 (n.s.)	.08: 22.7 (n.s.)	.10: 26.4 (n.s.)	.12: 29.5 (n.s.)	.16: 37.9 (n.s.)	.20: 45.8 (*4)	.24: 50.8 (n.s.)	.32: 64.6 (n.s.)	
DOLOMITI/2SC EXCEED AN857 2SC (scelta consigliata) (recommended option)	B12T..N FOR STANDARD FITTINGS	.04: 18.2 (n.s.)	.05: 19.0 (n.s.)	.06: 20.6 (n.s.)	.08: 23.5 (n.s.)	.10: 27.1 (n.s.)	.12: 31.1 (n.s.)	.16: 39.1 (n.s.)	.20: 48.7 (n.s.)	.24: 56.2 (n.s.)	.32: 71.0 (n.s.)	
	B1SC FOR STANDARD FITTINGS	.04: 16.2 (n.s.)	.05: 18.0 (n.s.)	.06: 20.0 (n.s.)	.08: 23.3 (n.s.)	.10: 27.6 (n.s.)	.12: 30.3 (n.s.)	.16: 37.9 (n.s.)				

° I DIAMETRI DI PRESSATURA INDICATI SONO VALIDI ANCHE PER LE VERSIONI **FOREVER e EVERGREEN**

° CRIMPING DIAMETERS REPORTED IN THIS DOCUMENT ARE VALID ALSO FOR **FOREVER AND EVERGREEN** VERSIONS

SPIRAL HOSES
Tubi spiralati

NOMINAL BORE	DN	5	6	8	10	12	16	19	25	31	38	51
INTERNAL DIAMETER	inches	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"	2"
	mm	4.8	6.4	7.9	9.5	12.8	16	19	25.4	31.8	38.1	50.8
TEKNOSPIR/4SP EN856 4SP (impieghi severi) (severe applications) Nota / Note :	B9R FOR STANDARD FITTINGS		.04: 19.2 (21)		.06: 23.2 (23)	.08: 26.3 (27)	.10: 29.8 (31)	.12: 33.5 (36)	.16: 41.8 (48)	.20: 54.6 (54)	.24: 58.5 (62)	.32: 74.0 (64)
	KB4SH FOR INTERLOCK FITTINGS					.10: 31.0 (14 in. 47.5out)	.12: 33.9 (15 in. 52 out.)	.16: 41.5 (17 in. 67 out.)				
	B5K FOR STANDARD FITTINGS				.06: 25.8 (n.s.)	.08: 28.5 (n.s.)	.10: 32.9 (n.s.)	.12: 36.0 (n.s.)	.16: 43.5 (n.s.)	B5Q06 57.0 (n.s.)		
	HB4NS FOR HYPERSPIRAL FITTINGS				.06: 26.5 (n.s.)	.08: 27.8 (n.s.)	.10: 33.9 (n.s.)	.12: 37.5 (n.s.)	.16: 46.5 (n.s.)			
	HB6NS FOR HYPERSPIRAL FITTINGS								.20: 58.3 (n.s.)	.24: 64.5 (n.s.)		
TEKNOSPIR/4SH EN856 4SH (impieghi severi) (severe applications) Nota / Note :	KB4SH FOR INTERLOCK FITTINGS						.10: 31.8 (14 in. 47.5out)	.12: 33.9 (15 in. 52 out.)	.16: 41.5 (17 in. 67 out.)	.20: 44.8 (21.5 in. 74 out.)	.24: 50.8 (22 in. 81 out.)	.32: 74.2 (29 in. 85 out.)
	B4SH FOR STANDARD FITTINGS								.20: 47.2 (54)	.24: 58.0 (62)	.32: 70.5 (64)	
	B5K FOR STANDARD FITTINGS							.12: 36.0 (n.s.)	.16: B5Q06 43.7 (n.s.)	54.0 (n.s.)		
	HB4NS FOR HYPERSPIRAL FITTINGS						.10: 34.5 (n.s.)	.12: 37.5 (n.s.)	.16: 46.7 (n.s.)	.20: 55.5 (n.s.)	.24: 62.5 (n.s.)	

SPIRAL HOSES
Tubi spiralati

NOMINAL BORE	DN	5	6	8	10	12	16	19	25	31	38	51
INTERNAL DIAMETER	inches	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"	2"
	mm	4.8	6.4	7.9	9.5	12.8	16	19	25.4	31.8	38.1	50.8
TEKNOSPIR/12 EN856 R12 SAE 100 R12 Nota / Note :	B9R FOR STANDARD FITTINGS				.06: 23.0 (23)	.08: 26.5 (27)	.10: 30.4 (31)	.12: 34.0 (36)	.16: 41.9 (48)	.20: 52.9 (54)	.24: 58.5 (62)	
	B4SH FOR STANDARD FITTINGS										.24: 58.9 (62)	.32: 70.6 (64)
	B5K FOR STANDARD FITTINGS				.06: 26.2 (n.s.)	.08: 27.6 (n.s.)	.10: 32.3 (n.s.)	.12: 35.8 (n.s.)	.16: B5Q06 43.5 (n.s.)	57.0 (n.s.)		
	HB4NS FOR HYPERSPIRAL FITTINGS				.06: 26.1 (n.s.)	.08: 27.5 (n.s.)	.10: 33.5 (n.s.)	.12: 37.3 (n.s.)	.16: 46.5 (n.s.)			
	HB6NS FOR HYPERSPIRAL FITTINGS								.20: 58.3 (n.s.)	.24: 64.5 (n.s.)		
TEKNOSPIR/13 EN856 R12 SAE 100 R13 Nota / Note :	KB4SH FOR INTERLOCK FITTINGS							.12: 34.7 (15 in. 52 out.)	.16: 42.2 (17 in. 67 out.)	.20: 49.8 (21.5 in. 74 out.)		
	KBH13 FOR INTERLOCK FITTINGS										.24: 59.7 (22 in. 81 out.)	.32: 78.2 (29 in. 85 out.)
	HB4NS FOR HYPERSPIRAL FITTINGS							.12: 38 (n.s.)	.16: 46.5 (n.s.)	.20: HB6NS24 55.5 (n.s.)	64.5 (n.s.)	
TEKNOSPIR/15 EN856 R12 SAE 100 R15 Nota / Note :	KB4SH FOR INTERLOCK FITTINGS							.12: 33.9 (15 in. 52 out.)	.16: 41.5 (17 in. 67 out.)			
	KBH13 FOR INTERLOCK FITTINGS									.20: 53.3 (21.5 in. 74 out.)	.24: 61.3 (22 in. 81 out.)	.32: 77.4 (29 in. 85 out.)
	HB4NS FOR HYPERSPIRAL FITTINGS						.10: 34.5 (n.s.)	.12: 37.5 (n.s.)	.16: 46.7 (n.s.)			
	HB6NS FOR HYPERSPIRAL FITTINGS									.20: 57.8 (n.s.)	.24: 64.5 (n.s.)	

SPIRAL HOSES
Tubi spiralati

NOMINAL BORE	DN	5	6	8	10	12	16	19	25	31	38	51
INTERNAL DIAMETER	inches	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"	2"
	mm	4.8	6.4	7.9	9.5	12.8	16	19	25.4	31.8	38.1	50.8
EVEREST/3000	B9R FOR STANDARD FITTINGS										.20: 51.8 (62)	.24: 58.5 (62)	.32: coming soon (64)
	B5K FOR STANDARD FITTINGS										B5Q06 57 (n.s.)		
	HB6NS FOR HYPERSPIRAL FITTINGS										.20: 58.3 (n.s.)	.24: 64.5 (n.s.)	
EVEREST/4000	B9R FOR STANDARD FITTINGS						.08: 26.5 (27)	.10: 30.4 (31)	.12: 34.0 (36)	.16: 41.9 (48)	.20: 53.2 (54)	.24: coming soon (62)	.32: coming soon (64)
	B5K FOR STANDARD FITTINGS						.08: 27.6 (n.s.)	.10: 32.3 (n.s.)	.12: 35.8 (n.s.)	.16: B5Q06 43.5 (n.s.)	54.0 (n.s.)		
	HB4NS FOR HYPERSPIRAL FITTINGS						.08: 27.5 (n.s.)	.10: 33.5 (n.s.)	.12: 37.3 (n.s.)	.16: 46.5 (n.s.)	.20: 55.5 (n.s.)	.24: 62.5 (n.s.)	
EVEREST/5000	KB4SH FOR INTERLOCK FITTING								.12: 33.9 (15 in. 52 out.)	.16: 41.3 (17 in. 67 out.)	.20: 49.8 (21.5 in. 74 out.)		
	KBH13 FOR INTERLOCK FITTINGS											.24: 59.7 (22 in. 81 out.)	.32: 78.2 (29 in. 85 out.)
	B9R FOR STANDARD FITTINGS						.08: 26.3 (27)	.10: 29.2 (31)	.12: 33.2 (36)	.16: 41.6 (48)	.20: 52.1 (54)		
	B5K FOR STANDARD FITTINGS						.08: 28.5 (n.s.)	.10: 32.9 (n.s.)	.12: 36 (n.s.)	.16: B5Q06 43.5 (n.s.)	54.0 (n.s.)		
	HB4NS FOR HYPERSPIRAL FITTINGS						.08: 27.8 (n.s.)	.10: 33.9 (n.s.)	.12: 37.5 (n.s.)	.16: 46.5 (n.s.)	.20: HB6NS24 55.5 (n.s.)	64.5 (n.s.)	

SPIRAL HOSES
Tubi spiralati

NOMINAL BORE	DN	5	6	8	10	12	16	19	25	31	38	51
INTERNAL DIAMETER	inches	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"	2"
	mm	4.8	6.4	7.9	9.5	12.8	16	19	25.4	31.8	38.1	50.8
EVEREST/6000	KB4SH FOR INTERLOCK FITTING					.10: 31.0 (14 in. 47.5out)	.12: 33.9 (15 in. 52 out.)	.16: 41.6 (17 in. 67 out.)				
	KBH13 FOR INTERLOCK FITTING							.20: 53.3 (21.5 in. 74 out.)	.24: 60.5 (22 in. 81 out.)	.32: 77.4 (29 in. 85 out.)		
	HB4NS FOR HYPERSPIRAL FITTINGS			.06: 25.8 (n.s.)	.08: 27.8 (n.s.)	.10: 33.9 (n.s.)	.12: 37.5 (n.s.)	.16: 46.7 (n.s.)				
	HB6NS FOR HYPERSPIRAL FITTINGS							.20: 57.8 (n.s.)	.24: 64.5 (n.s.)			
	B9R FOR STANDARD FITTINGS		.04: coming soon (21)		.06: 23.2 (23)	.08: 26.5 (27)	.10: 29.2 (31)	.12: 33.5 (36)	.16: 41.8 (48)			
EVEREST/6000 4C * B5K and B9R ferrules are suitable for applications reaching a maximum of 350Bar	KB4SH FOR INTERLOCK FITTING						.12: 33.2 (15 in. 52 out.)	.16: 40.2 (17 in. 67 out.)	.20: 50.2 (21.5 in. 74 out.)			
	HB4NS FOR HYPERSPIRAL FITTINGS						.12: 37 (n.s.)	.16: 45 (n.s.)	.20: 54.2 (n.s.)			
	B5K* FOR STANDARD FITTINGS						.12: 36.2 (n.s.)	.16: B5Q06 43.4 (n.s.)	53.4 (n.s.)			
	B9R* FOR STANDARD FITTINGS						.12: 33.6 (36)	.16: 40.1 (48)	.20: 51 (54)			

SPIRAL HOSES
Tubi spiralati

NOMINAL BORE	DN	5	6	8	10	12	16	19	25	31	38	51
INTERNAL DIAMETER	inches	3/16"	1/4"	5/16"	3/8"	1/2"	5/8"	3/4"	1"	1.1/4"	1.1/2"	2"
	mm	4.8	6.4	7.9	9.5	12.8	16	19	25.4	31.8	38.1	50.8
EVEREST/7300	KB4SH FOR INTERLOCK FITTING							.12: 33.9 (15 in. 52 out.)	.16: 41.6 (17 in. 67 out.)			
	KBH13 FOR INTERLOCK FITTING									.20: 53.3 (21.5 in. 74 out.)		
TEKNOBLAST AS/NZS 4233.2	WB4 FOR WATERBLAST-FITTINGS				.06: 24.4 (15 in. 47 out.)	.08: 28.2 (16 in. 52 out.)	.12: 38.6 (19 in. 54 out.)					
TEKNOBLAST PLUS AS/NZS 4233.2	WB4 FOR WATERBLAST-FITTINGS				.06: 24.6 (15 in. 47 out.)	.08: 29.1 (16 in. 52 out.)	.12: 38.9 (19 in. 54 out.)	.16: 41.5 (17 in. 57 out.)				
TEKNOBLAST SUPERB AS/NZS 4233.2	WB6 FOR WATERBLAST-FITTINGS					.08: -	.12: 41.2 (19 in. 54 out.)					

Nota: Data la larga tolleranza ammessa sulle dimensioni dei tubi, le quote di pressatura espresse sono indicative, si consiglia pertanto di utilizzare sempre i tamponi passa non passa per verificare il giusto collasso del codolo.

Note